

## NOTES

- A. A CONSTRUCTION FENCE MUST BE PLACED AROUND A TREE OR GROVE BEYOND THE EDGE OF THE ROOT ZONE. THE FENCE SHALL BE PLACED BEFORE PHYSICAL DEVELOPMENT STARTS AND REMAIN IN PLACE UNTIL PHYSICAL DEVELOPMENT IS COMPLETE. THE FENCE SHALL MEET THE FOLLOWING:
- 1. THE FENCE SHOULD BE A FOUR FOOT (4') TALL ORANGE PLASTIC OR SNOW FENCE, SECURED TO SIX FOOT (6') TALL METAL POSTS, DRIVEN TWO FEET (2') INTO THE GROUND. HEAVY 12 GAUGE WIRE SHALL BE STRUNG BETWEEN EACH POST AND ATTACHED TO THE TOP AND MIDPOINT OF EACH POST. COLORED TREE FLAGGING INDICATING THAT THIS AREA IS A TREE PROTECTION ZONE IS TO BE PLACED EVERY FIVE (5') LINEAR FEET ON THE FENCE TO ALERT CONSTRICTION CREWS OF SENSITIVE NATURE OF THE AREA. Β. WITHIN THE PROTECTED ROOT ZONE OF EACH TREE, THE FOLLOWING DEVELOPMENT SHALL NOT BE PERMITTED: 1. CONSTRUCTION OR PLACEMENT OF NEW BUILDINGS 2. GRADE CHANGE OR CUT AND FILL, EXCEPT WHERE HAND EXCAVATION IS APPROVED WITHIN THE SUBMITTAL OF AN ARBORIST'S REPORT, AS PART OF APPLICATION APPROVAL. 3. NEW IMPERVIOUS SURFACES 4. TRENCHING FOR UTILITIES, IRRIGATION, OR DRAINAGE. 5. STAGING OR STORAGE OF ANY KIND. 6. VEHICLE MANEUVERING OR PARKING.